


## Specification Sheet

Part Number: MB4SHA10C2



Adhesive Base, 1.12" x 1.12", .18" Max Tie Width, .15" Hole Dia, PA66, White, 100/pkg

<b>Article Number</b>	151-29203
<b>Type</b>	MB4SHA
<b>Color</b>	White (WH)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• 2-way opening for use with 18 through 50 pound cable ties to provide stability when securing bundles.</li><li>• Secures using the adhesive backing and/or with one screw.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton's 2 way, adhesive fastened mounting base is used with 18 through 50 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by inserting one screw through the center of the mount.
<b>Short Description</b>	Adhesive Base, 1.12" x 1.12", .18" Max Tie Width, .15" Hole Dia, PA66, White, 100/pkg

**Global Part Name**

MB4SHA-PA66-WH

**Length L (Imperial)**

1.12

**Length L (Metric)**

28.3

**Fixation Method**

Screw Mounting and Adhesive

**Width W (Imperial)**

1.12

**Width W (Metric)**

28.3

**Cable Ties**

T18 - T50

**Height H (Imperial)**

0.23

**Height H (Metric)**

5.8

**Cable Tie Width Max (Imperial)**

0.18

**Cable Tie Width Max (Metric)**

4.6

**Mounting Hole Diameter D (Imperial)**

0.15

**Mounting Hole Diameter D (Metric)**

3.9 mm

**Mounting Hole Diameter D Max (Metric)**

3.9

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut**

PA66

**Adhesive**

Synthetic rubber with base of polyethylene foam

**Flammability**

UL 94 V2 (excluding adhesive)

**Adhesive Operating Temperature**

-4°F to +122°F (-20°C to +50°C)

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**ROHS Complaint**

Yes

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

**Package Quantity(Imperial)**

100

**Package Quantity (Metric)**

100

**Customs Number**

3926909987

**Content Unit(BMEcat)**

pcs.